

# Sobo Degreaser

## Heavy Duty Oil Degreaser



**A general purpose heavy duty aqueous degreaser. Ideal for the degreasing of engineering components, work shops, industrial floors and similar areas contaminated by heavy oil and grease.**

### KEY PROPERTIES

An aqueous blend of biodegradable surfactants that quickly lift and separate oil contamination from industrial components.  
Water rinsable to provide an oil free clean surface.

Designed to remove oils, greases and lapping slurry.

Heavy oil  
degreaser

Biodegradable

Water  
rinsable

### APPLICATION

Designed for use in either a contact wipe, dip, immersion or spray on application. Allow a contact time of 2 – 3 minutes before rinsing surfaces with water.

Recommended dilution rate is 4%.

Dilutions below 1:2 are not classified as hazardous.

### TECHNICAL DATA

|               |                    |
|---------------|--------------------|
| Appearance    | Pale Yellow Liquid |
| SG            | 1.08               |
| VOC Content   | Zero               |
| BOD/COD 5 day | 72%                |

**AVAILABLE PACK SIZES** 1000 litre, 200 litre, 25 litre and 4 x 5 litre.

**SAFE HANDLING AND STORAGE** Store in original containers and avoid extremes of temperature.

For guidance on handling and disposal see

[Material Safety Data Sheet.](#)



Linton  
Business Park,  
Gourdon,  
Aberdeenshire,  
Scotland UK

**Tel:** +44(0)  
1561  
361515  
**Fax:** +44(0)  
1561  
361001