

Tunnel and Spray Wash Cleaning

Range

MSDS

VOC Content

Risk Phrases



The move away from using greenhouse gas producing cleaning solvent has started!

Sobo LF is solvent free, VOC free and environmentally friendly. Used in high pressure spray tunnels and power wash systems to provide an oil free clean surface.

KEY PROPERTIES

Sobo LF is a rust inhibited quick break aqueous cleaning fluid that is non emulsifiable (quick break), low foaming, inhibited and offering no hazard to painted surfaces, acrylics, non-ferrous metals and soft sealants.

Quick Break

Low Foam

Rust Inhibited

APPROVALS

- Rust Inhibited – AMS 1526B
- Separator Friendly – pr EN 858

APPLICATION

Suitable for use in spray wash systems such as tunnels, parts washers and steam cleaners.

Dilute between 2 – 5% depending upon the degree of soiling and the level of corrosion inhibition required.

Dilutions below 1:1 are not classified as hazardous.

TECHNICAL DATA

SG	1.03	VOC Content	Free
pH	10.5 – 11.5	BOD/COD 5 day	72%

AVAILABLE PACK SIZES 1000Ltr, 20Ltr, 4×5Ltr and Wipe Format

SAFE HANDLING AND STORAGE

Store in original containers and avoid extremes of temperature. For guidance on handling and disposal see [Material Safety Data Sheet](#).

